

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**


Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11) **EP 0 832 561 A2**

(12)

**EUROPEAN PATENT APPLICATION**

(43) Date of publication:  
01.04.1998 Bulletin 1998/14

(51) Int. Cl.<sup>6</sup>: **A01N 25/12**, **A01N 25/26**,  
**C02F 1/50**

(21) Application number: **97202345.1**

(22) Date of filing: **25.07.1997**

(84) Designated Contracting States:  
**AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC**  
**NL PT SE**  
Designated Extension States:  
**AL LT LV RO SI**

(30) Priority: **30.07.1996 GB 9615944**

(71) Applicant: **EASTMAN KODAK COMPANY**  
**Rochester, New York 14650 (US)**

(72) Inventors:  
• **Batts, Gregory Nigel**  
**Harrow, HA1 4TY (GB)**

• **Moore, Christopher Peter**  
**Harrow, HA1 4TY (GB)**  
• **Leeming, Karen**  
**Harrow, HA1 4TY (GB)**  
• **Wettling, Danielle**  
**71102 Chalon-Sur-Saone (FR)**

(74) Representative:  
**Nunney, Ronald Frederick Adolphe**  
**Kodak Limited,**  
**Patent Departement (W92)-3A,**  
**Headstone Drive**  
**Harrow, Middlesex HA1 4TY (GB)**

(54) **A material, method and apparatus for inhibiting microbial growth in an aqueous medium**

(57) A biocidal material comprises a biocide immobilised in a porous inorganic polymer network such as a sol-gel matrix. The polymer may be coated on an inorganic support e.g. pumice stones. The material can be used for inhibiting microbial growth in an aqueous medium e.g. the wash water of a photoprocessing system. The material can be housed in a flow-through container.




FIG. 6

EP 0 832 561 A2

**Description****Field of the Invention**

5 The invention relates to a material, method and apparatus for inhibiting microbial growth in an aqueous medium.

**Background of the Invention**

10 Microbial growth occurs in many systems in which aqueous media such as water, aqueous solutions and aqueous dispersions are employed.

For example, significant biofouling can occur in many areas of photoprocessing systems and, in particular, where low flow rate washes and water recycling is used. The problem may be overcome by adding biocides to the wash water tanks when bacterial biofilm formation becomes evident visually. However at this point the biocides may not work and even at quite high concentrations are not particularly effective because the bacteria have attached to surfaces to form colonies which have built up in layers. Hence, any biocide in solution can only reach the outer biofilm layer and not the inner layers of the biofilm which are protected. Furthermore, widespread use of such biocides is not desirable because they are relatively expensive and toxic chemicals which require specialised disposal to protect the environment.

Alternative methods of inhibiting bacterial growth in aqueous media involve the gradual release of a biocide through interaction with water e.g. by leaching.

20 US-A-4 552 591 describes a biocidal composition for inhibiting microbial growth in oil field waters which comprises a biocide and a solid, particulate adsorbent therefor. The biocides are conventional water soluble compounds traditionally used in the treatment of oil field waters e.g. 2-methyl-4-isothiazolin-3-one which are adhered to a known adsorbent e.g. diatomaceous earth. The compositions avoid the personal and environmental contamination which can result from spillage of the biocide used previously in liquid form. After addition to oil field waters, such compositions release the biocide through leaching.

**Problem to be Solved by the Invention**

30 A problem associated with the prior art methods and materials for inhibiting bacterial growth in aqueous media using biocides is that biocide is released in the media.

Furthermore, there is a need for a method and materials in which the biocide is only used on demand when the bacteria are present.

Methods and materials which reduce the exposure of operators to toxic biocides are also sought.

**Summary of the Invention**

The invention provides a biocidal material comprising a biocide and an inorganic carrier characterised in that the inorganic carrier is a porous inorganic polymer network in which the biocide is immobilised.

40 The invention also provides a method for inhibiting bacterial growth in an aqueous medium comprising contacting the aqueous medium with a biocidal material comprising a biocide and an inorganic carrier characterised in that the inorganic carrier is a porous inorganic polymer network in which the biocide is immobilised.

45 The invention also provides apparatus for inhibiting bacterial growth in an aqueous medium comprising a container having fluid inlet means and fluid outlet means said inlet and outlet means communicating with an inner chamber such that, when the apparatus is in use, fluid entering the inner chamber through the inlet means flows through the chamber and leaves the container through the outlet means characterised in that the inner chamber holds a biocidal material comprising a biocide and an inorganic carrier characterised in that the inorganic carrier is a porous inorganic polymer network in which the biocide is immobilised.

**Advantageous Effect of the Invention**

50 The invention removes the need for conventional dosing of biocides in solution, either directly or by gradual release, which has many drawbacks.

The biocide is only used on demand when the bacteria are present.

The direct exposure of operators to toxic biocides is minimised.

55 The invention is able to utilise inexpensive, readily available inorganic supports.

## Brief Description of the Drawings

Figure 1 is a schematic representation of apparatus used in evaluating the materials of the invention.

Figure 2 is a graphical representation of results achieved using the invention in accordance with Example 1 described hereafter.

Figure 3 is a graphical representation of results achieved using the invention in accordance with Example 2 described hereafter.

Figure 4 is a graphical representation of results achieved using the invention in accordance with Example 3 described hereafter.

Figure 5 is a graphical representation of results achieved using the invention in accordance with Example 4 described hereafter.

Figure 6 is a schematic representation of apparatus for use in performing the method of the invention.

Figure 7 is a schematic representation of the use of the apparatus shown in Figure 4.

## Detailed Description of the Invention

Suitable inorganic polymer networks include those derived from sol-gel materials, silicon nitride, metal esters e.g. acetates, nitrates, phosphates and ormosils (organically modified silicates)

Examples of suitable materials are referred to in "Sol-gel Science", by C.J. Brinker and G.W. Scherer, Academic Press, 1990, Chapters 2-3.

The preparation of inorganic e.g. silica glasses through the low temperature "sol-gel" synthesis is known. For example, see Chem. Rev. 1990, 90, 33-72 "The Sol-Gel Process" by L.L. Hench and J.K. West.

An amorphous matrix of the glassy material may be prepared by the room temperature polymerisation of suitable monomers, usually metal alkoxides. The polymerisation of metal alkoxide mixtures results in a transparent porous solid (xerogel) with surface areas of up to hundreds of square metres per gram and having small pores e.g. from 0.5 to 500nm. The low temperature glass synthesis allows doping of the inorganic glass with organic molecules e.g. a chemically sensitive dye.


The sol-gel glass has a cage-like porous molecular structure in which a single doping molecule can be isolated in an individual cage, even at high concentrations of additive. Molecules trapped in sol-gel glasses can interact with diffusible solutes or components in an adjacent liquid or gas phase in the pore space.

The sol-gel matrix may comprise one or more of  $\text{SiO}_2$ ,  $\text{TiO}_2$  and  $\text{ZrO}_2$ . In a preferred embodiment of the invention, a  $\text{SiO}_2/\text{TiO}_2$  sol-gel matrix is used. Preferably, the mole ratio of Si:Ti in the sol-gel glass is from 90:10 to 50:50, more preferably from 80:20 to 60:40.

Suitable types of biocide include those described in "Microbiocides for the Protection of Materials", W. Paulus, published by Chapman Hall, 1993. They are agents capable of killing or inhibiting the multiplication of microorganisms such as bacteria, yeasts, fungi, algae and lichens. Examples include heterocyclic N,S compounds, compounds with activated halogen groups and quaternary ammonium salts

Preferred biocides include those currently employed in the treatment of photoprocessing systems e.g. isothiazolinones.

Examples of isothiazolinone biocides are those having the structure




wherein


R represents hydrogen, alkyl, aryl, alkaryl and aralkyl; and,

$\text{R}^1$  and  $\text{R}^2$  independently represent hydrogen, halogen, alkyl, or  $\text{R}^1$  and  $\text{R}^2$  taken together represent the atoms necessary to complete a fused carbocyclic ring, preferably a 5- or 6-membered ring e.g. a benzene ring.


Preferred biocides include those having the following structures:



wherein R³ is an alkyl group having from 4 to 20 carbon atoms or an aryl group having from 6 to 20 carbon atoms;




wherein R⁵ and R⁶ are selected from hydrogen and halogen, and R⁴ is an alkyl group having from 5 to 20 carbon atoms; and,




wherein each of R⁷, R⁸ and R⁹ is hydrogen or an alkyl group providing a total of from 2 to 20 carbon atoms; R¹⁰ is substituted or unsubstituted alkyl or aryl e.g. phenoxyethyl; and, Y is any suitable counter anion e.g. halide.


Specific examples of commercially available isothiazolinone biocides include Proxel™ (manufactured by Zeneca):




Promexal™ (manufactured by Zeneca):




Kathon™ (manufactured by Rohm and Haas):




10 Other commercially available biocides are: Bronopol™ (manufactured by Boots):




20 Domiphen™ bromide (manufactured by Ciba-Geigy):




30 Vantocil™ (manufactured by Zeneca):



40 Densil S™ (manufactured by Zeneca):




50 Biocides which are hydrophobically modified Proxel™ and Kathon™ have been prepared having the following structures:



$R^3 = -(CH_2)_7CH_3$  (Compound 1)

$R^3 = -(CH_2)_{15}CH_3$  (Compound 2)



$R^4 = -(CH_2)_7CH_3$ ,  $R^5 = H$ ,  $R^6 = Cl$  (Compound 3)

$R^4 = -(CH_2)_{17}CH_3$ ,  $R^5 = H$ ,  $R^6 = Cl$  (Compound 4)

$R^4 = -(CH_2)_7CH_3$ ,  $R^5 = H$ ,  $R^6 = H$  (Compound 5)

$R^4 = -(CH_2)_7CH_3$ ,  $R^5 = Cl$ ,  $R^6 = Cl$  (Compound 6)

Many commercially available biocides are soluble in aqueous media and an increase in their hydrophobicity is required to convert them into the preferred hydrophobic compounds for use in the invention.

It is preferred that the biocides having a log P of at least 1.5 wherein P represents the partition coefficient between n-octanol and water defined as follows

$$P = \frac{[\text{biocide}]_{\text{octanol}}}{[\text{biocide}]_{\text{water}}}$$

Log P is a well known term used in literature on biocides. As used herein, it provides a measure of the hydrophobicity of the biocide.

A variety of commercial and hydrophobically-modified biocides have been studied. Partition coefficients between octanol and water have been determined at 25°C by UV/visible absorption. First, the calibration curve of each biocide was determined as optical density ( $OD_{\text{abs}}$ ) versus concentration of biocide in  $\mu\text{g/g}$  (ppm) of water for the predominantly water-soluble materials and  $\mu\text{g/g}$  of octanol for the predominantly oil-soluble biocides.

A known amount of biocide was placed in a glass vessel containing either 10ml of water or 10ml of octanol depending on the solubility of the biocide. An equal volume of the other solvent was added and the glass vessel sealed. The vessel was shaken vigorously for a few minutes and then every few hours for more than 48 hours. Each mixture was placed in a sealed separating funnel and left for a further 24 hours. The water phase of each mixture was removed and the UV/visible spectra run against water with appropriate dilutions to bring absorbance between 0 and 1.5 for the commercial biocides and the octanol fractions were examined for the hydrophobically modified biocides.

The following partition coefficients shown in Table 1 were determined.

Table 1

Biocide	P
Promexal™	~4.5
Vantocil™	~0.3
Domiphen™	~50
Kathon™	~1
Proxel™	~0*
Compound 1	>330
Compound 3	>560
Compound 2	>130
Compound 4	>480

\* i.e. there was almost no biocide in the oil phase.

The log P value of the biocides which are used in the invention is preferably at least 1.5, more preferably at least 2.0.

Preferably, the amount of biocide used is from 5 to 35 mole percent, more preferably from 20 to 30 mole percent based on the metal alkoxide or other precursor used to construct the inorganic polymer network.

Preferably, the inorganic polymer network is coated on a support. Preferred support materials are those to which the inorganic polymer readily adheres.

Inorganic support materials are advantageous. Many provide the additional benefits of low cost and physical robustness. Suitable materials include pumice, clay, sand, gravel, chalk, zeolites and glass. Such materials give the further advantage of easy disposal and are potentially more stable over wide pH ranges than organic polymer-based systems.

Polymers suitable for use as support materials include any inert, water insoluble polymers having appropriate surface properties. Preferably, such polymer supports have a non-crystalline surface. Preferably, the polymer supports have a hydrophilic surface comprising groups such as -OH and -COOH.

Examples of suitable types of polymer from which suitable supports can be derived include ethenic polymers including polyolefins, polystyrene, polyvinyl chloride, polyvinyl acetate and acrylic polymers; and polymers formed by condensation reactions including polyesters, polyamides, polyurethanes, polyethers, epoxy resins, amino resins and phenol-aldehyde resins.

The support may take a variety of forms e.g. particulate, sheet or fibre. It may be porous or non-porous.

The thickness of the inorganic polymer network coating on the support may be from 10nm to 10µm, preferably from 50nm to 5µm.

In accordance with one method of preparing a material of the invention, a solution of the biocide is made in an organic solvent e.g. tetrahydrofuran or alcohol. The biocide solution is mixed with an alkoxide sol-gel forming pre-cursor. The pre-cursor containing the biocide may be coated on a support if required by any conventional coating means e.g. dipping, spinning and spraying. The pre-cursor containing the biocide is left for some hours e.g. from 4 to 6 hours, before removing the solvent, preferably under reduced pressure. Drying is preferably carried out in a vacuum oven at a temperature from 60 to 100°C.

In use, the aqueous medium is brought into contact with the biocidal material. Different ways of achieving contact include passing the aqueous medium through a container e.g. a column containing the material in particulate form, passing the aqueous medium through a filter of the material and passing the aqueous medium over the material in the form of a surface coating.

The invention is of particular use in photoprocessing systems. Such systems comprise stages for developing, fixing, bleaching and washing an exposed photographic material. Each stage requires apparatus for applying the appropriate aqueous processing solution to the photographic material. The apparatus may comprise means for supplying, removing and, possibly, recirculating such solutions.

The method of the invention may be used to inhibit microbial growth in the wash water or other solutions used in a photoprocessor.

Figure 6 is a schematic representation of apparatus for use in performing the method of the invention. The apparatus comprises a container 10 having fluid inlet means 11 and fluid outlet means 12 said inlet and outlet means 11, 12



communicating with an inner chamber 13 of the container. When the apparatus is in use, fluid entering the inner chamber through the inlet means 11 flows through the chamber 13 and leaves the container through the outlet means 12. The inner chamber 13 holds a biocidal material in accordance with the invention in the form of particles 14. A filter 15 to retain the particles is positioned at the top of the inner chamber to prevent loss of the particles from the device. The top of the container 10 is provided with plugs 16 for venting any gas which accumulates in the device.

Fluid entering the device flows down a central tube and subsequently flows up through the particles. The arrows indicate the direction of the flow of fluid through the device.

Figure 7 is a schematic representation of the use of the apparatus shown in Figure 6. A tank 20 containing water 21 is shown e.g. the wash water tank of a photoprocessor. Tubing 22 has an open end in the water 21 at the bottom of tank 20, the other end being connected to the inlet of a pump 23 outside the tank 20. Tubing 24 connects the outlet of the pump 23 to the inlet of a device 25 of the type shown in Figure 6. One end of tubing 26 is connected to the outlet of device 25 and the other end opens into the top of tank 20.


In use, water is pumped from the bottom of tank 20 through device 25 and back into tank 20 in a recirculation loop. The arrows indicate the direction of the flow of water around the loop.

The invention is further illustrated by way of example as follows.

### Preparation of Biocide

A Proxel™ analogue (Compound 2) was prepared in three steps from commercially available starting materials as outlined in Scheme 1.

**Scheme 1**



### Example 1

Compound 2, dissolved in a small quantity of tetrahydrofuran (THF), was added at 25%mol/mol to a 70/30 Si/Ti alkoxide sol-gel forming precursor ("liquid-coat", Merck ZLI 2132,1857). The mixture was coated onto pumice stones (Prolabo 26398293), leaving the sol in contact with the support for about 5 hours before removing the solvent under reduced pressure (14mm Hg) and drying in a vacuum oven. Analysis (IR, MS and elemental) of dried samples showed the presence of immobilised biocide.

Control (blank sol-gel) and active (immobilised biocide in sol-gel) coated pumice stones were tested in a nutrient broth containing  $\sim 10^4$  bacteria/ml (*Pseudomonas aeruginosa*). The control particles and active particles were each put separately into a 10cm glass column with screw-tight plastic adaptors and polypropylene nozzles. A nylon mesh filter

was put at the bottom and top of each column in between two rubber washers. The columns, all silicone rubber tubing, flasks and nutrient broth necessary to complete the flow circuit were sterilised by autoclaving at 120°C for >20 minutes. Each column was placed in circuit with 50ml of nutrient broth as shown in Figure 1. A shaking water bath held at 30°C was used to keep the 250ml wide-neck round-bottomed flasks containing the culture at this constant temperature. A small inoculum of pre-prepared bacterial culture was added to each flask to give a known number of bacteria/ml in the flask. At time zero, a small aliquot of the bacterial culture was removed from each flask for further counting/analysis and the pumps started to give a volume flowrate of 13.5ml/min. The flow direction was upwards through the stones.

Aliquots were removed from the reaction flask at time intervals of 0.5, 8 and 24 hours and the viable counts performed. These data are summarised in Figure 2. There is the usual lag phase as the bacteria become accustomed to the new medium, followed by a growth phase in each system. However, it is quite evident that the bacterial population is significantly lower in the active system, which shows a bactericidal effect compared to the control.

Differences could be seen visually between the active and control systems since solutions become more cloudy as bacterial populations increase due to light-scattering phenomena. Light scattering and perhaps UV absorption could be used to detect total number of bacteria, but, unlike plating, these techniques would not distinguish between viable and non-viable organisms.

In addition, the solutions were analysed after the experiment. None of the Compound 2 or obvious metabolites were detected by HPLC or mass spectrometry.

#### Example 2

An identical method to Example 1 was used except that porous clay beads (OBI, 8-16mm) were used in place of the pumice stones. Microbiological evaluation was carried out in a similar fashion to Example 1, and the data is given in Figure 3. This demonstrates that bacteriostatic activity is obtained for the Compound 2 immobilised in sol-gel coated on clay beads.

#### Example 3

An identical method to Example 1 was used except that Compound 3 was used in place of Compound 2. Microbiological evaluation was carried out in a similar fashion to Example 1, using untreated pumice stones (no sol-gel coating) and those having a sol-gel coating only (no biocide); the data are given in Figure 4. The data demonstrate that the biocidal activity of the hydrophobic biocide is maintained using immobilisation in sol-gel coated onto pumice stones.

#### Example 4

An identical method to Example 1 was used except that Compound 3 was used in place of Compound 2. The resultant active and control pumice stones were dried for 1 hour at 90°C and tested as described previously. The microbiological results in Figure 5 show that the drying treatment has removed any contribution from the blank sol-gel coating. In this case Compound 3 immobilised in sol-gel coated on pumice stones is strongly bactericidal.

#### Claims

1. A biocidal material comprising a biocide and an inorganic carrier characterised in that the inorganic carrier is a porous inorganic polymer network in which the biocide is immobilised.
2. A material according to claim 1 wherein the inorganic polymer network is a sol-gel matrix.
3. A material according to claim 2 wherein the sol-gel matrix is a  $\text{SiO}_2/\text{TiO}_2$  sol-gel matrix.
4. A material according to claim 3 wherein the mole ratio of Si:Ti in the sol-gel is from 80:20 to 60:40.
5. A material according to any one of the preceding claims wherein the biocide has the structure



wherein

R represents hydrogen, alkyl, aryl, alkaryl and aralkyl; and,  
 R¹ and R² independently represent hydrogen, halogen, alkyl, or R¹ and R² taken together represent the atoms necessary to complete a fused carbocyclic ring.

6. A material according to any one of the preceding claims wherein the inorganic polymer network is coated on a support.
7. A material according to claim 6 wherein the support is an inorganic support.
8. A material according to claim 6 or claim 7 wherein the support is a particulate support.
9. A method for inhibiting microbial growth in an aqueous medium comprising contacting the aqueous medium with a biocidal material according to any one of the preceding claims.
10. A method according to claim 9 wherein the aqueous medium is the wash water of a photoprocessing system.
11. Apparatus for inhibiting microbial growth in an aqueous medium comprising a container having fluid inlet means and fluid outlet means said inlet and outlet means communicating with an inner chamber such that, when the apparatus is in use, fluid entering the inner chamber through the inlet means flows through the chamber and leaves the container through the outlet means characterised in that the inner chamber holds a biocidal material according to any one of claims 1 to 8.




FIG. 1

FIGURE 2




FIGURE 3




FIGURE 4





FIGURE 5








FIG. 6





FIG. 7



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11) **EP 0 832 561 A3**

(12) **EUROPEAN PATENT APPLICATION**

(88) Date of publication A3:  
17.02.1999 Bulletin 1999/07

(51) Int. Cl.<sup>6</sup>: **A01N 25/12, A01N 25/26,  
C02F 1/50**

(43) Date of publication A2:  
01.04.1998 Bulletin 1998/14

(21) Application number: 97202345.1

(22) Date of filing: 25.07.1997

(84) Designated Contracting States:  
**AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC  
NL PT SE**  
Designated Extension States:  
**AL LT LV RO SI**

(30) Priority: 30.07.1996 GB 9615944

(71) Applicant: **EASTMAN KODAK COMPANY**  
Rochester, New York 14650 (US)

(72) Inventors:  
• **Batts, Gregory Nigel**  
Harrow, HA1 4TY (GB)

• **Moore, Christopher Peter**  
Harrow, HA1 4TY (GB)  
• **Leeming, Karen**  
Harrow, HA1 4TY (GB)  
• **Wettling, Danielle**  
71102 Chalon-Sur-Saone (FR)

(74) Representative:  
**Nunney, Ronald Frederick Adolphe**  
Kodak Limited,  
Patents, W92-3A,  
Headstone Drive  
Harrow, Middlesex HA1 4TY (GB)

(54) **A material, method and apparatus for inhibiting microbial growth in an aqueous medium**

(57) A biocidal material comprises a biocide immobilised in a porous inorganic polymer network such as a sol-gel matrix. The polymer may be coated on an inorganic support e.g. pumice stones. The material can be used for inhibiting microbial growth in an aqueous medium e.g. the wash water of a photoprocessing system. The material can be housed in a flow-through container.




FIG. 6

EP 0 832 561 A3



European Patent  
Office

## EUROPEAN SEARCH REPORT

Application Number  
EP 97 20 2345

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
X,P	EP 0 736 249 A (KODAK PATHE ;EASTMAN KODAK CO (US)) 9 October 1996 * claims * * page 2, line 52 - line 55 * * example 7 *	1-5,9-11	A01N25/12 A01N25/26 C02F1/50
X	EP 0 665 004 A (LUCKY LTD) 2 August 1995 * claims 1,6-8 *	1,2,6-9	
X	GB 1 590 574 A (ATOMIC ENERGY AUTHORITY UK) 3 June 1981 * claim 20 * * page 1, line 38 * * page 3, line 24 *	1,2,9	
A,D	US 4 552 591 A (MILLAR SCOTT W) 12 November 1985		
			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
			A01N B01J
The present search report has been drawn up for all claims			
Place of search		Date of completion of the search	Examiner
THE HAGUE		22 December 1998	Decorte, D
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 03 82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 97 20 2345

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

22-12-1998

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0736249 A	09-10-1996	FR 2732189 A	04-10-1996
		JP 8332488 A	17-12-1996
		US 5683826 A	04-11-1997
		US 5846555 A	08-12-1998
EP 0665004 A	02-08-1995	KR 9700745 B	18-01-1997
		JP 2775596 B	16-07-1998
		JP 8040830 A	13-02-1996
GB 1590574 A	03-06-1981	CH 639869 A	15-12-1983
		DE 2735392 A	09-02-1978
		FR 2360345 A	03-03-1978
		IE 45648 B	20-10-1982
		JP 53020411 A	24-02-1978
US 4552591 A	12-11-1985	NONE	